

## ClearFLEX™ 60 PVC Tubing Products

All ClearFLEX 60 PVC tubing products offer the following features:

- Crystal clarity for visible flow
- Compliance with USP Class VI and USDA standards
- Compliance with FDA CFR 21 for food packaging
- May be sterilized by autoclaving, gas or chemical methods (see page 3)

ClearFLEX 60 Cat. No.	Size, in.				Oper. Pressure, psig @ 73°F	Case Qty., ft.
	ID	x	OD	x Wall		
8160-4170	1/16		1/8	1/32	48	100
8160-4220	3/32		5/32	1/32	42	100
8160-4245	1/8		1/4	1/16	50	100
8160-4295	3/16		5/16	1/16	36	100
8160-4335	1/4		3/8	1/16	30	100
8160-4340	1/4		7/16	3/32	40	100
8160-4345	1/4		1/2	1/8	46	100
8160-4390	5/16		7/16	1/16	28	100
8160-4400	5/16		9/16	1/8	42	100
8160-4430	3/8		1/2	1/16	22	100
8160-4435	3/8		9/16	3/32	32	100
8160-4440	3/8		5/8	1/8	40	100
8160-4505	1/2		5/8	1/16	20	100
8160-4510	1/2		11/16	3/32	26	100
8160-4515	1/2		3/4	1/8	30	100
8160-4570	5/8		7/8	1/8	26	100
8160-2605	3/4		1	1/8	22	50
8160-2675	1		1-1/4	1/8	18	50
8160-2685	1		1-3/8	3/16	26	50
8160-2690	1		1-1/2	1/4	34	50
8160-2715	1-1/4		1-5/8	3/16	22	50
8160-2755	1-1/2		2	1/4	24	50
8160-2790	2		2-1/2	1/4	18	50

ClearFLEX V60 Cat. No.	Size, in.				Oper. Pressure, psig @ 73°F	Case Qty., ft.
	ID	x	OD	x Wall		
8160-2310	3/16		9/16	3/16	62	50
8160-2350	1/4		5/8	3/16	56	50
8160-2460	3/8		7/8	1/4	54	50
8160-2530	1/2		1-1/8	5/16	52	50
8160-2585	5/8		1-3/8	3/8	56	50
8160-2625	3/4		1-1/2	3/8	46	50
8160-2700	1		2	1/2	46	50

ClearFLEX M60 Cat. No.	Size, mm				Oper. Pressure, psig @ 73°F	Case Qty., ft.
	ID	x	OD	x Wall		
8160-0102	1.0		2.0	0.5	46	100
8160-0204	2.0		4.0	1.0	46	100
8160-0406	4.0		6.0	1.0	32	100
8160-0508	5.0		8.0	1.5	34	100
8160-0610	6.0		10.0	2.0	38	100
8160-0710	7.0		10.0	1.5	28	100
8160-0812	8.0		12.0	2.0	32	100
8160-0913	9.0		13.0	2.0	28	100
8160-1014	10.0		14.0	2.0	26	100
8160-1216	12.0		16.0	2.0	24	100
8160-1823	18.0		23.0	2.5	20	50
8160-2025	20.0		25.0	2.5	18	50

## ClearFLEX™ 60 Premium PVC Tubing

### Features and Benefits:

- Long service life – non-aging, non-oxidizing
- Smooth inner wall resists build-up
- Soft and flexible – easy to slip over fittings
- Tight bend radius
- Outstanding flex life

### Recommended Applications:

- Peristaltic pumps
- Lab and research work
- Media manufacture/transfer
- Food/beverage processing
- Condenser coolant lines
- Vapor transfer
- Toys

## ClearFLEX™ V60 Vacuum PVC Tubing

### Features and Benefits:

- Extra heavy wall
- Withstands full vacuum (30" Hg) at room temperature and 26" Hg at 140°F
- Excellent resistance to corrosive atmospheres
- Kink-proof

## ClearFLEX™ M60 Metric PVC Tubing

### Features and Benefits:

- All the advantages of ClearFLEX 60, but in metric sizes
- Eliminates leaky connections typical of "close-to-size" English-measure tubing



Authorized Distributor:

Aetna Plastics Corp. 1702 St. Clair Ave. Cleveland, Ohio 44114 • Tel: 800-634-3074  
216-781-4421 • Fax: 216-781-4474 • sales@aetnoplastics.com • www.aetnoplastics.com