



## FLEX™ GP70 PVC Tubing – Clear

### Features and Benefits:

- Clear and flexible
- Complies with FDA CFR 21 for food packaging
- Resists aging
- Resistant to a broad range of chemicals
- Excellent wearability
- Smooth inner wall; excellent flow characteristics
- Easy to connect
- Cost-effective alternative to ClearFLEX for applications that don't require regulatory compliances
- Light weight, yet tough and abrasion-resistant

### Recommended Applications:

- General-purpose chemical transfer and other applications not subject to regulatory requirements
- Suitable for use with foods and beverages
- Handles broad range of chemicals, gases and liquids

## FLEX™ GP70B PVC Tubing – Black

### Features and Benefits:

- More resistant to UV exposure than clear tubing
- Does not promote algae growth

### Recommended Applications:

- Outdoor applications
- Light-sensitive media
- Color coding of processing lines
- Secondary containment of other lines

FLEX GP70 (Clear) Cat. No.	FLEX GP70B (Black) Cat. No.	Size, in.			Oper. Pressure, psig @ 73°F	Case Qty., ft.
		ID	x OD	x Wall		
8200-4170		1/16	1/8	1/32	66	100
8200-4240		1/8	3/16	1/32	46	100
8200-4245	8242-4245	1/8	1/4	1/16	68	100
8200-4290		3/16	1/4	1/32	34	100
8200-4295	8242-4295	3/16	5/16	1/16	54	100
8200-4300		3/16	3/8	3/32	70	100
8200-4305		3/16	7/16	1/8	80	100
8200-4330		1/4	5/16	1/32	28	100
8200-4335	8242-4335	1/4	3/8	1/16	46	100
8200-4340		1/4	7/16	3/32	58	100
8200-4345	8242-4345	1/4	1/2	1/8	70	100
8200-4390	8242-4390	5/16	7/16	1/16	40	100
8200-4395		5/16	1/2	3/32	52	100
8200-4400		5/16	9/16	1/8	62	100
8200-4430	8242-4430	3/8	1/2	1/16	34	100
8200-4435		3/8	9/16	3/32	48	100
8200-4440	8242-4440	3/8	5/8	1/8	58	100
8200-4463		7/16	9/16	1/16	30	100
8200-4465		7/16	5/8	3/32	44	100
8200-4470		7/16	11/16	1/8	48	100
8200-4505	8242-4505	1/2	5/8	1/16	28	100
8200-4510		1/2	11/16	3/32	38	100
8200-4515	8242-4515	1/2	3/4	1/8	44	100
8200-4540		9/16	3/4	3/32	36	100
8200-4560		5/8	3/4	1/16	24	100
8200-4565		5/8	13/16	3/32	34	100
8200-4570	8242-4570	5/8	7/8	1/8	38	100
8200-2590		11/16	15/16	1/8	36	50
8200-2600		3/4	7/8	1/16	20	50
8200-2605	8242-2605	3/4	1	1/8	34	50
8200-4605		3/4	1	1/8	34	100
8200-2615		3/4	1-1/8	3/16	48	50
8200-2640		7/8	1-1/8	1/8	30	50
8200-2675	8242-2675	1	1-1/4	1/8	28	50
8200-4675		1	1-1/4	1/8	28	100
8200-2685		1	1-3/8	3/16	38	50
8200-2690		1	1-1/2	1/4	44	50
8200-2710		1-1/4	1-1/2	1/8	24	50
8200-2715		1-1/4	1-5/8	3/16	34	50
8200-2720		1-1/4	1-3/4	1/4	40	50
8200-2745		1-1/2	1-3/4	1/8	18	50
8200-2750		1-1/2	1-7/8	3/16	28	50
8200-2755	8242-2755	1-1/2	2	1/4	36	50
8200-2790	8242-2790	2	2-1/2	1/4	28	50
8200-2805		2-1/4	2-3/4	1/4	24	50
8200-2815	8242-2815	2-1/2	3	1/4	22	50
8200-2840	8242-2840	3	3-1/2	1/4	20	50

### NOTE:

The operating pressures for FLEX™ Tubing Products decrease as the temperature increases. The operating pressure for any given formulation and size at 125°F (52°C) is half that at 73°F (23°C).

Authorized Distributor:

Aetna Plastics Corp. 1702 St. Clair Ave. Cleveland, Ohio 44114 • Tel: 800-634-3074  
216-781-4421 • Fax: 216-781-4474 • sales@aetnaplastics.com • www.aetnaplastics.com