



FuelFLEX™ 65 PVC Fuel Tubing

Features and Benefits:

- Flexible and easy to install (65A durometer)
- Resists swelling and hardening
- Easy-to-identify transparent yellow

Recommended Applications:

- For intermittent use with petroleum-based products
- Fuel drain lines, vent tubes and overflow tubes
- Transfer of gasoline, heating oils, cutting compounds and coolants
- Lab handling of distillates
- NOT intended for use with foods or beverages

FuelFLEX 65 Cat. No.	Size, in.				Oper. Pressure, psig @ 73°F	Case Qty., ft.
	ID	x	OD	x Wall		
8365-4230	3/32		3/16	3/64	54	100
8365-4245	1/8		1/4	1/16	62	100
8365-4295	3/16		5/16	1/16	48	100
8365-4335	1/4		3/8	1/16	40	100
8365-4390	5/16		7/16	1/16	36	100
8365-4430	3/8		1/2	1/16	30	100
8365-4465	7/16		5/8	3/32	40	100
8365-4515	1/2		3/4	1/8	40	100
8365-4570	5/8		7/8	1/8	34	100
8365-2605	3/4		1	1/8	30	50

BraidFLEX™ 70N Braided PVC Tubing

Features and Benefits:

- Now complies with NSF-51
- Complies with FDA CFR 21 for food packaging
- Embedded braid prevents material entrapment, ensures easy cleaning
- Easy to bend into place
- Flexible; permits tight clamping for leakproof connections
- Maximum working pressure clearly printed on tubing
- Clear tubing allows full visual flow monitoring

Recommended Applications:

- Transfer lines
- Higher-pressure applications, including lab, food and beverage use
- Pneumatic circuitry
- Cell culture
- Use with insert/barbed fittings
- NOT recommended for vacuum applications

BraidFLEX 70N Cat. No.	Size, in.				Oper. Pressure, psig @ 73°F	Case Qty., ft.
	ID	x	OD	x Wall		
8470-4300	3/16		3/8	3/32	276	100
8470-7300	3/16		3/8	3/32	276	250
8470-4340	1/4		7/16	3/32	276	100
8470-7340	1/4		7/16	3/32	276	250
8470-4395	5/16		1/2	3/32	276	100
8470-4435	3/8		9/16	3/32	250	100
8470-7435	3/8		9/16	3/32	250	250
8470-4515	1/2		3/4	1/8	230	100
8470-7515	1/2		3/4	1/8	230	250
8470-4570	5/8		7/8	1/8	230	100
8470-7570	5/8		7/8	1/8	230	250
8470-2605	3/4		1	1/8	176	50
8470-7605	3/4		1	1/8	176	250
8470-2680	1		1-5/16	5/32	140	50
8470-7680	1		1-5/16	5/32	140	250
8470-2715	1-1/4		1-5/8	3/16	100	50
8470-2750	1-1/2		1-7/8	3/16	80	50
8470-2790	2		2-1/2	1/4	70	50

Authorized Distributor:

Aetna Plastics Corp. 1702 St. Clair Ave. Cleveland, Ohio 44114 • Tel: 800-634-3074
216-781-4421 • Fax: 216-781-4474 • sales@aetnoplastics.com • www.aetnoplastics.com