

New!

Thermoplastic Pressure Regulators

Permits Downstream Pressure Settings From 5 to 125 PSI

Designed for Higher Flow Capacities with Less System Pressure Loss



Materials of Construction and Piping Connections:

The standard connections are female NPT threaded ports. Socket, flanged and spigot connections are also available. Standard body materials are PVC and CPVC. Standard seal materials are FKM and EPDM. For other materials, including Natural Polypropylene, Kynar PVDF and PTFE, see catalogs PRH and PRHM.

Superior Features:

- Converts varying inlet pressure up to 150 PSI, to a stabilized, lower pre-set downstream pressure.
- Protects sensitive downstream instruments, tubing and filters against damage from overpressure/pressure surges; permits the entire system to operate safely and effectively.
- Downstream pressure settings adjustable from 5 to 125 PSI.
- Large surface area of its frictionless rolling diaphragm provides exceptional sensitivity.
- Free movement of the diaphragm on a balanced shaft assures smooth, accurate performance and reliable sealing for millions of cycles.
- Double U-cups prevent leakage along the shaft and eliminates the possibility of "creep".
- Optional gauge ports to assist with setting and monitoring pressure.
- For corrosive and ultra-pure liquid applications.
- Sizes: 3/4" and 1". For other sizes, see Catalogs PRH and PRHM.

Pressure Regulator Selection:

In the selection of a liquid pressure regulator, flow capacity with minimum system pressure loss are critical criteria, but it should be recognized that all similar-size competitive regulators do not provide similar performance levels. The new Series PRHM regulators provide not only higher set pressures and flow capacities with each model, but these are achieved with less pressure losses than with similar size competitive regulators. These lower pressure drop-offs can be seen from the performance curve chart shown on the next page.



PLAST-O-MATIC VALVES, INC.

1384 Pompton Avenue, Cedar Grove, New Jersey 07009-1095

(973) 256-3000 • Fax (973) 256-4745 • www.plastomatic.com

SERIES PRHM 3/4" & 1" PVC PRESSURE REGULATORS


Design:

Plast-O-Matic Series PRHM Pressure Regulators are designed to handle corrosive and ultra-pure liquids with inlet pressures up to 150 PSI at 75°F. Standard downstream set pressure range is 5 to 125 PSI. The normally-open regulators incorporate a poppet seat at the valve orifice to prevent sticking and affecting the sensing of the downstream line pressure. Also, one piece body construction and dual U-cup shaft seals help to eliminate internal leakage that could cause the set pressure to creep beyond a safe limit. A unique, large-surface, rolling diaphragm seal isolates the spring chamber from downstream pressure sensing liquid. This unique design, in conjunction with a pressure balanced shaft, assures smooth performance and stable control. **CAUTION:** Avoid quick closing valve downstream of a regulator to eliminate "water hammer" shock that can cause breakage.

Typical Performance Curves of Flow vs. Drop Off From Set Pressure:

Drop-off is the difference between the pressure regulator set pressure and the downstream pressure. Performance curves chart at right identifies the high flow capacities and the low pressure drop-off of Plast-O-Matic regulators which result in their greater sensitivity, finer adjustability and superior accuracy as compared to competitive models.

Dimensions:



Dim.	SIZE NPT or BSP	
	3/4"	1"
A	Inch 27/8 mm 73	Inch 27/8 mm 73
B	Inch 7 13/16 mm 190	Inch 7 13/16 mm 190
C	Inch 27/8 mm 73	Inch 27/8 mm 73
D	Inch 5 1/2 mm 140	Inch 5 1/2 mm 140

Series PRHM Model Number & Maximum Flow

Valve Size	Model Numbers		Flow Rates GPM*
	EDPM Seals	FKM Seals	
3/4"	PRHM075EP	PRHM075V	35
1"	PRHM100EP	PRHM100V	50

*Maximum Recommended

Operation:



Series PRHM pressure regulators prevent downstream pressure from exceeding the desired set pressure. Regulator will remain closed as long as set pressure is maintained. As equipment or valves downstream of regulator begin to open and demand flow, the downstream pressure begins to fall and the regulator begins to open. As valves or equipment downstream open further, the pressure regulator continues to open until the maximum opening is reached. As the process is reversed, downstream pressure begins to increase and the regulator starts closing. When the downstream pressure again reaches set pressure the regulator closes bubble-tight.

IMPORTANT: It should be noted from the preceding explanation that a pressure regulator does not maintain a specific downstream pressure, but *only* prevents the downstream pressure from exceeding a set point.

Typical 3/4" and 1" Pressure Regulators Performance Curves:

Flow Capacity vs. Pressure Drop-Off (PSI)

Comparison of Representative Plast-O-Matic Models with Competitors



The drop-off is the difference between the pressure regulator set pressure and the downstream pressure. NOTE: All data for these curves was collected from actual flow tests at Plast-O-Matic Valves, Inc., Cedar Grove, NJ, or manufacturer's published performance data. The measuring equipment used was the same for all regulators tested, and the relative results between different models are considered to be an accurate portrayal of the data.

NOTE: Refer to Catalog PRH and PRHM for information on other sizes and materials.

Authorized Distributor:

**Aetna Plastics Corp. 1702 St. Clair Ave. Cleveland, Ohio 44114 • Tel: 800-634-3074
216-781-4421 • Fax: 216-781-4474 • sales@aetnaplastics.com • www.aetnaplastics.com**