

Fast Pack - Valve/Actuator Packages



Series 94/Type 57 Butterfly Valve Features

- UL-508 Listed electric actuator
- Type-57 PVC Body, PP Disc, EPDM or FKM seals , Wafer Style
- 120 VAC Capacitor run reversing Type Motor
- Thermal Overload Protection with Auto Reset
- De-clutchable manual override
- Visual Position indicator
- 5 second cycle time
- Mechanical Brake supplied as standard for 4" T-57 butterfly valves
- Type 4X Engineered Resin Enclosure
- 2 End of Travel Limit Switches
- 2 Additional Limit switches for Indication
- Complete Factory assembled and tested actuated valve package



Series 94/Type 21 Ball Valve Features

- UL-508 Listed electric actuator
- Type-21 PVC with EPDM or FKM seals, Tru-Union Ball Valve
- T-21 1/2" - 2" supplied with both Socket and Threaded ends, 2-1/2" - 3" Socket only
- 120 vac Capacitor run reversing Type Motor
- Thermal Overload Protection with Auto Reset
- De-clutchable manual override
- Visual Position indicator
- 5 second cycle time
- Type 4X Engineered Resin Enclosure
- 2 End of Travel Limit Switches
- 2 Additional Limit switches for Indication
- Complete Factory assembled and tested actuated valve package

Valve Type	Size	Actuation Model	Input Voltage	L.R. Amps	Duty Cycle
T-21	1/2" - 2"	A94M2WJ	115 vac	0.5	100%
T-21	2-1/2" - 3"	B94M2WJ	115 vac	0.8	75%
T-57	1-1/2" - 2"	A94M2WJ	115 vac	0.5	100%
T-57	2-1/2" - 3"	B94M2WJ	115 vac	0.8	75%
T-57	4"	B94BRM2WJ	115 vac	0.8	75%

Authorized Distributor:
Aetna Plastics Corp. 1702 St. Clair Ave. Cleveland, Ohio 44114 • Tel: 800-634-3074
216-781-4421 • Fax: 216-781-4474 • sales@aetnoplastics.com • www.aetnoplastics.com