


TI 2-1/2" - 4"

Diaphragm Valves



TI Diaphragm 2-1/2" - 4"

Specifications
Sizes: 2-1/2" - 4"
Body Material: PVDF
Bonnet Material: PPG
Diaphragm: 3-Layer EPDM/PVDF/PTFE with Palladium Titanium Insert
Compressor Pin: Palladium Titanium
Compressor Insert: Palladium Titanium
Fasteners: Titanium

Parts TI (2-1/2" - 4")

PARTS			
NO.	DESCRIPTION	PCS.	MATERIAL
1	Body	1	PVDF
2	Bonnet	1	PPG
3	Diaphragm	1	PTFE
3a	Diaphragm Metal Insert	1	PALLADIUM TITANIUM
4	Cushion	1	EPDM
5	PVDF Gas Barrier	1	PVDF
6	Compressor	1	PVDF
8	Stem	1	COPPER ALLOY (C3604)
8a	Indicating Rod	1	304 SS
9	Sleeve	1	COPPER ALLOY (C36004)
10	Handwheel	1	PP
11	Gauge Cover	1	POLYCARBONATE
12	Name Plate	1	PVC
13	Retaining Ring C-Type	1	304 SS
14	O-Ring (A)	1	EPDM
15	O-Ring (B)	1	EPDM
16	Thrust Ring (A)	1	UHMWPE
17	Thrust Ring (B)	1	UHMWPE
18	Bolt, Nut, Washer	4 Sets	TITANIUM
20	Stopper (A)	1	COPPER ALLOY (C3604)
88	Bonnet Plug	1	TITANIUM
89	Compressor Pin	1	PALLADIUM TITANIUM
90	Stud Bolt, Nut, Washer	4 Sets	TITANIUM
94	Metal Compressor Insert	1	PALLIDIUM TITANIUM
1a	Body Insert Nut	4	TITANIUM

For exploded view drawings refer to page 64

Features and Benefits (2-1/2"- 4")

- Durable Corrosion Resistant PPG Bonnet
- Solid Molded PVDF Flanged Body
- 3-Layer EPDM/PVDF/PTFE Diaphragm
- All Titanium Body to Bonnet Fasteners
- Palladium Titanium Compressor pin, Compressor Insert and Diaphragm Insert

Sample Specification 2-1/2"- 4"

All Ti Type-14 diaphragm valves shall be of solid molded PVDF Flanged body and PPG bonnet, weir type with round body to bonnet sealing design. Valves shall be supplied standard with 3-layer EPDM Cushion/PVDF Gas Barrier/PTFE diaphragm, Titanium body to bonnet bolts, studs, molded in body inserts, nuts, and washers. Diaphragms shall feature Palladium Titanium threaded connection stud that shall connect to the PVDF compressor via Palladium Titanium metal insert. Compressor pin shall be Palladium Titanium. Face to Face dimensions shall conform to Type-G. PVDF conforming to ASTM D3222 Cell Classification Type II. Valves shall be rated to 150 psi at 70° F as manufactured by Asahi/America, Inc.

Authorized Distributor:

Aetna Plastics Corp. 1702 St. Clair Ave. Cleveland, Ohio 44114 • Tel: 800-634-3074
 216-781-4421 • Fax: 216-781-4474 • sales@aetnaplastics.com • www.aetnaplastics.com