

## Electrically Actuated Ball Valve Type 131-133

Designed to be modular, the 130 series electrically actuated ball valve is adaptable to a variety of conditions and applications. The type 130 series, our premium actuated valve, is available in PVC, CPVC, Polypropylene, and PVDF materials. With the optional positioner, it goes from being a simple on/off valve to a precision flow control device, integrated into systems controlled by PLCs and other computerized instrumentation.

### Advantages:

- Size range 3/8" to 4"
- 110-230VAC auto-detecting or 24V AD/DC
- Manual override on actuator
- Available in PVC, CPVC, polypropylene, and PVDF
- PTFE seat
- EPDM or FPM seals
- UL certified
- NSF approval

### Options:

- Limit switches
- Fail safe back-up battery
- Silicone free version
- Positioner (4-20mA, 1-10V)
- ASI control



### Technical Data

**Size Range:** 1/2" to 4"

**End connectors:** socket, flanged, spigot (PVDF and PP only), and threaded to 2" (up to 4" in PVC and CPVC)

**Standards:** ATSM

**Nominal pressure:** cemented and fusion versions 232 PSI, flanged and threaded 150 PSI

**Power consumption:** 3/8"-2" 28 Watts, 2 1/2"-4" 32 Watts

**Voltage:** 110-230VAC or 24V AC/DC

**Duty cycle:** 3/8"-2" 100%, 2 1/2"-4" 50%

**Materials:** PVC, CPVC, polypropylene and PVDF

**Seal:** EPDM or FPM

**Seat:** PTFE

Authorized Distributor:

**Aetna Plastics Corp. 1702 St. Clair Ave. Cleveland, Ohio 44114 • Tel: 800-634-3074**  
**216-781-4421 • Fax: 216-781-4474 • sales@aetnaplastics.com • www.aetnaplastics.com**