


GF Piping Systems Datasheet

Ball check valves

Type 360 True Union Ball Check Valve PVC With solvent cement sockets ASTM




Model:

- For easy installation and removal
- Ball is sealing at a minimum water column 2m
- Vibration free even at high flow velocity

Size	DN [mm]	PN	Cv-value [gal (US) /min]	EPDM Part No.	FPM Part No.	lbs/each	z [inch]	D [inch]	L [inch]	L2 [inch]
3/8	10	240	12	161 360 561	161 360 571	0.271	2.91	1.77	4.41	2.48
1/2	15	240	11	161 360 562	161 360 572	0.271	2.64	1.77	4.41	2.48
3/4	20	240	23	161 360 563	161 360 573	0.452	3.15	2.09	5.16	2.95
1	25	240	27	161 360 564	161 360 574	0.701	3.35	2.52	5.59	3.11
1 1/4	32	240	50	161 360 565	161 360 575	1.155	4.02	3.07	6.54	3.50
1 1/2	40	240	63	161 360 566	161 360 576	1.854	3.94	3.62	6.69	3.74
2	50	240	97	161 360 567	161 360 577	3.296	4.88	4.57	7.91	4.53

Type 360 True Union Ball Check Valve CPVC With solvent cement sockets ASTM



Model:

- For easy installation and removal
- Ball is sealing at a minimum water column of 2 m
- Vibration free even at high flow velocity

Size	DN [mm]	PN	Cv-value [gal (US) /min]	EPDM Part No.	FPM Part No.	lbs/each	z [inch]	D [inch]	L [inch]	L2 [inch]
3/8	10	240	12	163 360 561	163 360 571	0.306	2.91	1.77	4.41	2.48
1/2	15	240	11	163 360 562	163 360 572	0.306	2.64	1.77	4.41	2.48
3/4	20	240	23	163 360 563	163 360 573	0.509	3.15	2.20	5.16	2.95
1	25	240	27	163 360 564	163 360 574	0.791	3.35	2.64	5.55	3.11
1 1/4	32	240	50	163 360 565	163 360 575	1.305	4.02	3.23	6.54	3.50
1 1/2	40	240	63	163 360 566	163 360 576	2.094	3.94	3.86	6.69	3.74
2	50	240	97	163 360 567	163 360 577	3.724	4.88	4.72	7.91	4.53

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.

Authorized Distributor:

**Aetna Plastics Corp. 1702 St. Clair Ave. Cleveland, Ohio 44114 - Tel: 800-634-3074
216-781-4421 - Fax: 216-781-4474 - sales@aetnaplastics.com - www.aetnaplastics.com**