



GF Piping Systems Datasheet

Angle seat check valves



Type 304 Translucent Y-Check Valve PVC Transparent body with solvent cement spigots ASTM

Model:

- For horizontal or vertical installation
- Leakproof even at minimum pressure
- Specific gravity of piston approx. 2 kg/dm³

Size	DN [mm]	PN	Cv-value [gal (US) /min]	EPDM Part No.	FPM Part No.	lbs/each
½	15	150	7	192 304 006	192 304 031	0.397
¾	20	150	13	192 304 007	192 304 032	0.551
1	25	150	23	192 304 008	192 304 033	0.849
1 ¼	32	150	34	192 304 009	192 304 034	1.279
1 ½	40	150	51	192 304 010	192 304 035	2.138
2	50	150	79	192 304 011	192 304 036	3.252
3	80	150	175	192 304 013	192 304 038	7.604

Size	D [inch]	L [inch]	L1 [inch]	L2 [inch]	H [inch]
½	1.69	5.63	5.87	1.46	2.56
¾	1.85	6.30	6.54	1.77	2.95
1	2.20	6.85	7.09	1.85	3.54
1 ¼	2.52	7.40	7.64	0.24	4.02
1 ½	3.23	8.07	8.31	2.13	4.84
2	3.74	8.86	9.09	2.48	5.67
3	4.09	12.24	12.64	3.54	8.03

The technical data are not binding and not expressly warranted characteristics of the goods. They are subject to change. Our General Conditions of Sale apply.