

# Fast Pack - Valve/Actuator Packages

SHIPS IN  
24 HRS !



SHIPS IN  
24 HRS !



## Series 92/Type 57 Butterfly Valve Features

- UL-508 Listed electric actuator
- Type-57 PVC Body, PP Disc, EPDM or FKM seals, Wafer Style
- 120 VAC Capacitor run reversing Type Motor
- Thermal Overload Protection with Auto Reset
- De-clutchable manual override
- Visual Beacon Position indicator
- 10 Second Cycle time 1-1/2" - 4", 25 second cycle time 6" & 8" T-57
- Mechanical brake supplied as standard for 6" and 8" T-57
- Type 4X/7 Diecast Aluminum w/ Powdercoat finish Enclosure
- 2 End of Travel Limit Switches
- 2 Additional Limit switches for Indication
- PPG Mounting bracket with 304 SS coupling and hardware 304 SS mounting bracket, coupling and hardware sizes 6" & 8"
- Complete Factory assembled and tested actuated valve package

## Series 92/Type 21 Ball Valve Features

- UL-508 Listed electric actuator
- Type-21 PVC with EPDM or FKM seals, Tru-Union Ball Valve
- T-21 1/2" - 2" supplied with both Socket and Threaded ends, 2-1/2" - 4" Socket only
- 120 VAC Capacitor run reversing Type Motor
- Thermal Overload Protection with Auto Reset
- De-clutchable manual override
- Visual Beacon Position indicator
- 10 second cycle time
- Type 4X/7 Diecast Aluminum w/ Powdercoat finish Enclosure
- 2 End of Travel Limit Switches
- 2 Additional Limit switches for Indication
- PPG Mounting bracket with 304 SS coupling and hardware
- Complete Factory assembled and tested actuated valve package

Valve Type	Size	Actuation Model	Input Voltage	L.R. Amps	Duty Cycle
T-21	1/2" - 3"	S92M2XWJ	115 vac	0.5	100%
T-21	4"	A92M2XWJ	115 vac	0.8	75%
T-57	1-1/2" - 4"	S92M2XWJ	115 vac	0.5	100%
T-57	6"	B92BRM2XWJ	115 vac	0.8	100%
T-57	8"	C92BRM2XWJ	115 vac	1.0	50%

Authorized Distributor:

Aetna Plastics Corp. 1702 St. Clair Ave. Cleveland, Ohio 44114 • Tel: 800-634-3074  
216-781-4421 • Fax: 216-781-4474 • sales@aetnaplastics.com • www.aetnaplastics.com